




The RG1676 is designed for arc and noise suppression in heavy duty applications requiring greater magnitudes of power dissipation. Due to its mass and weight, mounting holes are provided at either end of the case to permit secure mounting to a chassis.

Its configuration lends itself to stacking for maximum utilization of available space. Special lead lengths are available. Other values of wattage and resistance or capacitance and voltage are also available.



Maximum peak surge voltage is 1½ time the rated DC voltage.
All leads #18 AWG MTW except -24 through -33 and -61 which are 16# AWG MTW.

RG1676 PN.	RESISTANCE OHMS	TOLERANCE %	POWER WATTS	CAPACITY MFD	TOLERANCE %	VDC VOLTS	VAC VOLTS	METAL OXIDE VARISTOR PN.	RG1676 LEAD LENGTH (IN.)	CIRCUIT NO.
RG1676-1	100	10	10	1.00	10	1000	480	N/A	24	1
RG1676-2	100	10	10	.50	10	1000	480	N/A	24	1
RG1676-3	10	10	2	1.00	10	600	250	N/A	25	1
RG1676-4	220	10	10	.47	10	600	250	N/A	25	1
RG1676-5	220	10	1	.50	10	600	250	N/A	25	1
RG1676-6	100	10	1	.10	10	2000	480	N/A	24	1
RG1676-7	100	10	3	2.00	10	600	250	N/A	25	1
RG1676-8	100	10	2	.47	10	600	250	N/A	25	1
RG1676-9	220	10	1	.47	10	600	250	N/A	25	1
RG1676-10	220	10	5	2.00	10	600	250	N/A	25	1
RG1676-11	220	10	1	.50	10	600	120	V130LA1	24	2
RG1676-12	220	10	2	.50	10	1000	480	N/A	24	1
RG1676-13	220	10	1	.47	10	1000	480	N/A	24	1
RG1676-14	220	10	1	.47	10	600	120	V130LA1	24	2
RG1676-15	220	10	1	1.00	10	600	250	N/A	25	1
RG1676-16	220	10	10	.50	10	1000	480	N/A	24	1
RG1676-17	100	10	2	1.00	10	600	250	N/A	25	1
RG1676-18	220	10	5	.47	10	1000	480	N/A	48	1
RG1676-19	220	10	2	1.00	10	400	120	N/A	24	1
RG1676-20	100	10	2	2.00	20	600	250	N/A	18	1
RG1676-21	10	10	5	1.00	10	1000	480	N/A	24	1
RG1676-22	220	10	2	.50	10	400	120	N/A	24	1
RG1676-23	220	10	.5	.50	10	400	120	N/A	24	1
RG1676-24	220	10	10	.50	10	1000	480	N/A	36	1
RG1676-25	220	10	.5	.50	10	400	120	N/A	36	1
RG1676-26	47	10	2	.10	10	1000	480	N/A	12	1
RG1676-27	47	10	2	.10	10	2000	480	N/A	12	1
RG1676-28	47	10	2	.10	10	1000	250	V250LA2	24	2
RG1676-29	200	10	10	.50	10	1000	480	N/A	24	1
RG1676-30	100	10	2	.47	10	600	250	V300LA2	12	2
RG1676-31	22	10	1	.10	10	1000	480	N/A	24	1
RG1676-32	100	10	10	.25	10	1000	480	N/A	24	1
RG1676-33	50	10	10	.25	10	1000	480	N/A	24	1
RG1676-34	220	10	5	.47	10	1000	480	N/A	48	1
RG1676-35	220	10	.5	.50	10	600	250	N/A	36	1
RG1676-36	220	10	1	.47	10	600	120	V130LA1	120	2
RG1676-37	100	10	10	.18	10	1000	480	N/A	24	1
RG1676-38	50	10	10	.50	10	600	250	V250LA2	24	2
RG1676-39	50	10	10	.50	10	1000	480	V480LA40A	24	2
RG1676-40	15	10	10	.25	10	1000	480	N/A	24	1
RG1676-41	33	10	1	.10	10	2000	480	N/A	24	1
RG1676-42	15	10	5	.50	10	1000	480	N/A	24	1
RG1676-43	47	10	2	.47	20	600	250	N/A	12	1
RG1676-44	100	10	10	.30	10	1000	480	N/A	24	1
RG1676-45	220	10	5	.50	10	1500	480	N/A	24	1
RG1676-46	10	10	5	.22	20	1000	480	N/A	24	1
RG1676-47	220	10	1	.25	10	1000	480	V480LA40A	24	2
RG1676-48	100	10	2	.10	10	2000	480	N/A	24	1
RG1676-49	100	10	3	.10	10	1000	480	N/A	24	1
RG1676-50	470	10	10	.25	10	1000	480	V480LA40A	24	2
RG1676-51	220	10	10	.50	10	1000	480	V480LA40A	24	2
RG1676-52	22	10	10	.10	10	600	250	N/A	24	1
RG1676-53	75	10	10	.50	10	1000	480	N/A	24	1
RG1676-54	47	10	2	2.00	10	600	250	N/A	24	1
RG1676-55	10	10	2	.47	10	600	250	N/A	25	1
RG1676-56	50	10	10	.50	10	600	250	V250LA40A	24	2
RG1676-57	100	10	1	.50	10	600	120	V130LA1	24	2
RG1676-58	220	10	2	.10	10	2000	275	V275LA40A	24	2
RG1676-59	220	10	2	.47	10	600	250	V250LA40A	24	2
RG1676-60	220	10	5	1.00	10	1000	480	N/A	24	1
RG1676-61	68	10	10	.25	10	1000	480	N/A	24	1
RG1676-62	220	10	5	.25	10	1000	480	N/A	24	1
RG1676-63	50	10	10	1.00	10	600	250	N/A	24	1
RG1676-64	220	10	10	2.00	10	600	250	N/A	24	1
RG1676-65	10	10	10	.50	10	1000	480	N/A	24	1
RG1676-66	820	10	10	.47	10	1000	480	N/A	10	1