

## EXAMPLES OF APPLICATION-SPECIFIC DESIGNS

### Pendant Switch

Remote hand held pushbutton switch with coiled cord that extends to approximately 3'.

**Circuit:** SPNO-DB  
**Rating:** 10 amps Resistive @ 28VDC  
**Button:** Black nylon  
**Housing:** Black nylon  
**Cord:** Black polyurethane, 28 AWG  
**U2-098**



### Coiled Cord Switch

Remote hand held pushbutton switch with 72" coiled cord. Sealed against dust and moisture.

**Rating:** 10 amps Resistive @ 28VDC  
**Button:** Green nylon  
**Housing:** Black anodized aluminum  
**Cable:** 6' extended, 18 AWG  
**P3-80012**



### Grip Switch Assembly

Switch is built into a grip designed for rugged outdoor use. Automotive type connector.

**Circuit:** SPNC-DB  
**Rating:** 10 amps Resistive @ 28VDC  
**Button:** Red nylon  
**Housing:** Black nylon  
**Cord:** Black polyurethane, 18 AWG  
Left and right hand operation with various connection types available.  
**U2-076**



### Pendant Switch

Remote hand held pushbutton switch with 24" coiled cord that extends to approximately 15'. Terminated with a 1/4" right angle molded phone plug (optional).

**Circuit:** SPNO-DB  
**Rating:** 5 amps Resistive @ 28VDC  
**Button:** Black nylon  
**Housing:** Black nylon  
**Cord:** Black polyurethane, 22 AWG  
**U2-034**



### Pendant Switch

Remote hand held pushbutton switch with 7.0" +/- 1.0" wire leads.

**Circuit:** SPST Alternate Action  
**Rating:** 5 amps Resistive @ 28VDC  
**Button:** Red nylon  
**Housing:** Black nylon  
**Cord:** Black polyurethane, 18 AWG  
**U2-150**



### Pendant Switch

Remote hand held pushbutton switch with coiled cord that extends to approximately 20'. Terminated with a connector.

**Circuit:** SPNO-DB  
**Rating:** 5 amps Resistive @ 28VDC  
**Button:** Red nylon  
**Housing:** Black nylon  
**Cord:** Black neoprene, 18 AWG  
**Connector:** Deutsch  
**U2-096**

